



www.tirexfabrics.com





Partnership with BASF: Commitment to Quality and Innovation

At Tirex, we are proud to operate under the licensed expertise of BASF, a global leader in chemical production. This partnership enhances our commitment to providing high-quality, reliable, and innovative textile solutions, ensuring that every product we create meets the highest standards of performance and sustainability.

Material composition			FTP - 900
	Measurement methods	unit	
finish cover	In two cases-pvdf y/n	pvdf lacquer	pvdf lacquer
base fabric	DIN ISO 2076	polyster	polyster
yarn construction	DIN ISO 2060	dtex	1100
wight	EN ISO 2286-2	g/m2	900
Fabric thickness (mm)		mm	0.8
Mechanical properties			
tensile strenght(w/f)	DIN EN ISO 1421/V1	n/50mm	4300/4300
tear resistance (w/f)	DIN EN ISO 1421/V1	n	500/500
adhesion	PA 09.03	n/cm	25
Physical properties			
cold resistance	DIN EN 1876-1	c	-40
heat resistance	PA 07.04	c	70
fire resistance	Classification	DIN 4102-1:B1	
width (m)		m	3
uv transmision	DIN EN 410	%	0



7
year
warranty



Get in Touch with Us

Main Office: Schipkauer Str. 1, 01987 Schwarzheide, Germany

Tel: +49 35752 60

Cz Office : Mlýnské údolí 664, Jihoceský kraj ,Trhové Sviny Czech

Tel: +420 397 511 106 / **Email:** tirexfab@tirexfabrics.com



