





Partnership with BASF: Commitment to Quality and Innovation

At Tirex, we are proud to operate under the licensed expertise of BASF, a global leader in chemical production. This partnership enhances our commitment to providing high-quality, reliable, and innovative textile solutions, ensuring that every product we create meets the highest standards of performance and sustainability.

Material composition

FTP - 1050



7 year warranty

	Measurement methods	unit	
finish cover	In two cases-pvdf y/n	pvd lacquer	pvd lacquer
base fabric	DIN ISO 2076	polyester	polyester
yarn construction	DIN ISO 2060	dtex	1670
wight	EN ISO 2286-2	g/m2	1050
Fabric thickness (mm)		mm	0.9

Mechanical properties

tensile strenght(w/f)	DIN EN ISO 1421/V1	n/50mm	6000/5800
tear resistance (w/f)	DIN EN ISO 1421/V1	n	900/800
adhesion	PA 09.03	n/cm	25

Physical properties

cold resistance	DIN EN 1876-1	c	-40
heat resistance	PA 07.04	c	70
fire resistance	Classification		DIN 4102-1:B1
width (m)		m	3
uv transmsion	DIN EN 410	%	0



Get in Touch with Us

Main Office: Schipkauer Str. 1, 01987 Schwarzheide, Germany

Tel: +49 35752 60

Cz Office : Mlýnské údolí 664, Jihoceský kraj ,Trhové Sviny Czech

Tel: +420 397 511 106 / **Email:** tirexfab@tirexfabrics.com

